# GSL

## **Emergency Open Space**

### 3w or 1w available Also available as Self-test

Connection and installation. All parts will through the **40mm** ceiling cut out.

C € 1 X LUXEON 1W

Once recessed the LED device will be low profile and discrete on any surface.

#### INTRODUCTION


#### BATTERY PACKS

This is a complete quick and easy solution for LED mains/emergency applications. It is designed to be used as a stand-alone unit to pass through a 40mm cut out. Consisting of the **BC/LED/CC** module technology and **LED/20/3** device the kit fits together with simple connections provided by irreversible plug/socket. The kit comes only with Nickel Metal Hydride (NiMH) 2.1Ah battery pack.

- Carvana

(4 WAY)

Please see separate Battery Specification Sheet for details.



**Recessed LED c/w mounting bezel.** 

MAXIMUM SPACING 0.2 LUX			
Mounting Height	To Wall	Between Fittings	
2.5m	4.5	10.4	
3.0m	4.9	11.6	
4.0m	5.4	13.4	
5.0m	5.6	14.6	
6.0m	5.6	15.3	

MAXIMUM SPACING 1 LUX			
Mounting Height	To Wall	Between Fittings	
2.5m	2.6	6.7	
3.0m	2.5	6.9	
4.0m	2.1	7.0	
5.0m	0.3	6.4	
6.0m	n/a	4.4	

#### Technical Details: BC8 Ceiling Recessed 1/3 - Watt LED Kit

MODEL NUMBER	BC8/M3/S	BC8/M3/W
Finish	Silver	White
Battery	2.1 Ah 3 Cell 3.6V NiMH triangular pack	
Charge Current	100	mA
Load	LED/20/110/L1	c/w 1W Luxeon
Output Current	350mA	
Ballast Lumen Output	100%	
Emergency Duration	3 Hours	
Discharge Current	500mA	
Cut Off Voltage	2.7V	
Recharge Time	24 Hours	
Case Temperature	70'C module/50'C battery	
Supply Voltage	230/240V 50/60Hz	
Operation Mode	Switchable maintained/non maintained	
Mounting Hole Size	40mm	
Emitter Luminous Flux	32 Lumen (minimum)*	
Colour Temperature	>6000K	
* = Please refer to office for latest output figures (subject to increase)		


MAXIMUM SPACING 0.2 LUX			
Mounting Height	To Wall Between Fittings		
2.0m	2.5m	6.0m	
2.5m	3.2m	7.0m	
3.0m	3.6m	7.9m	
4.0m	4.1m	9.6m	
5.0m	4.5m	10.8m	

MAXIMUM SPACING 1 LUX					
Mounting Height	To Wall	o Wall Between Fittings			
2.0m	2.0m	4.5m			
2.5m	-	4.1m			
3.0m	-	3.2m			
4.0m	-	-			
5.0m	-	-			

#### ORDERING CODES

Pack Details	NO. OF CELLS	FINISH	LED
BC8/M3/S	3	Silver	1W
BC8/M3/W	3	White	1W
BC8/3W/M3/S	3	Silver	3W
BC8/3W/M3/W	3	White	3W

#### Illuminance (Lx)



#### Dimensions

